
TECHNISCHE DATEN

- BODENRECYCLER -

TECHNISCHE DATEN

| ObLX | Empfohlene Größe des Trägergeräts [to] | | Gewicht [kg]* | Breite [cm] | Höhe [cm] | Tiefe [cm] | Schaufelvolumen [m³]** | Siebfläche [m²] | empf. Ölmenge [l/min] | max. Öldruck [bar] |
|---------------|--|----------|---|-------------|-----------|------------|------------------------|-----------------|-----------------------|--------------------|
| | Bagger | Radlader | | | | | | | | |
| B120-3 | 16-24 | 7-13 | F20S: 1.700 F40S: 1.720 F80C: 1.500 F100C: 1.400 | 160 | 136 | 137 | 1,1 | 0,95 | 200 | 280 |
| B180-3 | 20-28 | 9-15 | F20S: 2.300 F40S: 2.370 F80C: 2.100 F100C: 2.000 | 223 | 136 | 137 | 1,7 | 1,5 | 200 | 280 |
| B180-4 | 24-36 | 13-19 | F20S: 3.170 F40S: 3.250 F80C: 2.720 F100C: 2.620 | 227 | 163 | 149 | 2,17 | 1,9 | 280 | 280 |

| IdFX | Empfohlene Größe des Trägergeräts [to] | | Gewicht [kg]* | Breite [cm] | Höhe [cm] | Tiefe [cm] | Schaufelvolumen [m³]** | Siebfläche [m²] | empf. Ölmenge [l/min] | max. Öldruck [bar] |
|---------------|--|----------|--|-------------|-----------|------------|------------------------|-----------------|-----------------------|--------------------|
| | Bagger | Radlader | | | | | | | | |
| B90-2 | 5-12 | ab 1,5 | F30S: 615 F30SC: 675 F40S: 605 F40SC: 655 | 125 | 95 | 105 | 0,35 | 0,50 | 30-75 | 300 |
| B150-2 | 8-14 | ab 3 | F30S: 810 F30SC: 945 F40S: 765 F40SC: 880 | 185 | 95 | 105 | 0,55 | 0,80 | 40-75 | 300 |

SCREEN-MODUL



| Scheiben Typ | Dicke der Scheiben | Scheiben-abstand |
|--------------|--------------------|------------------|
| F30S | 16 mm | 34 mm |
| F40S | 16 mm | 44 mm |

SCREEN-CRUSH-MODUL



| Scheiben Typ | Dicke der Scheiben | Scheiben-abstand |
|--------------|--------------------|------------------|
| F30SC | 16 mm | 34 mm |
| F40SC | 16 mm | 44 mm |